

SAFETY DATA SHEET

Sharkbite Wet Wax

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Trade name: Sharkbite Wet Wax
Product no.: 1436
Unique formula identifier (UFI): V707-S3YS-ERC8-93PR

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture: Brightener
Uses advised against: None known.

1.3. Details of the supplier of the safety data sheet

Company and address: **Everbrand Sweden AB**
Ågårdsvägen 4
335 73 Hillerstorp
Sweden
+46(0)370 615530
E-mail: hello@everbrandsweden.com
Revision: 21/01/2025
SDS Version: 1.0

1.4. Emergency telephone number

Healthcare professionals: Dial 0344 892 0111 to reach The National Poisons Information Service (NPIS) (24 hour service)
General public:
England - Dial 111 to reach NHS 111 (24 hour service)
Scotland - Dial 112 to reach NHS 24 (24 hour service)
Wales - Dial 111 or 0845 4647 to reach NHS Direct (24 hour service)
See section 4 "First aid measures".

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Flam. Liq. 3; H226, Flammable liquid and vapour.
Aquatic Chronic 3; H412, Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram(s):



Signal word: Warning

Hazard statement(s):	Flammable liquid and vapour. (H226) Harmful to aquatic life with long lasting effects. (H412)
Precautionary statement(s):	
General:	If medical advice is needed, have product container or label at hand. (P101) Keep out of reach of children. (P102)
Prevention:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)
Response:	In case of fire: Use water mist/carbon dioxide/alcohol-resistant foam to extinguish. (P370+P378)
Storage:	Store in a well-ventilated place. Keep cool. (P403+P235)
Disposal:	Dispose of contents/container in accordance with local regulation (P501)
Hazardous substances:	propan-2-ol
Additional labelling:	EUH208, Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. UFI: V707-S3YS-ERC8-93PR

2.3. Other hazards

Additional warnings:	This product contains a vPvB and/or PBT substance: Octamethylcyclotetrasiloxane (PBT / vPvB) This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.
-----------------------------	--

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
propan-2-ol	CAS No.: 67-63-0 EC No.: 200-661-7 UK-REACH: Index No.: 603-117-00-0	5-10%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	
Polydimethylsiloxane, diquaternary	CAS No.: 134737-05-6 EC No.: UK-REACH: Index No.:	1-3%	Aquatic Chronic 2, H411	
(2-methoxymethylethoxy)propanol	CAS No.: 34590-94-8 EC No.: 252-104-2 UK-REACH: Index No.:	1-3%		[1]

2-(2-butoxyethoxy)ethanol	CAS No.: 112-34-5 EC No.: 203-961-6 UK-REACH: Index No.: 603-096-00-8	<1%	Eye Irrit. 2, H319	[1], [3]
1,2-benzisothiazol-3(2H)-one	CAS No.: 2634-33-5 EC No.: 220-120-9 UK-REACH: Index No.: 613-088-00-6	<0.05%	Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 (SCL: 0.05 %) Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=1)	
Octamethylcyclotetrasiloxane	CAS No.: 556-67-2 EC No.: 209-136-7 UK-REACH: Index No.: 014-018-00-1	<0.05%	Flam. Liq. 3, H226 Repr. 2, H361f Aquatic Chronic 1, H410 (M=10)	[3], [5], [6], [7]

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit.

[3] According to UK REACH, Annex XVII, the substance is subject to restrictions.

[5] Substance is included in the Candidate List of substances of very high concern (SVHC).

[6] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[7] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information:

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation:

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact:

IF ON SKIN: Wash with plenty of water and soap. Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. If skin irritation occurs: Get medical advice/attention.

Eye contact:

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during transport.

Ingestion:

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor.

Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns:

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact. Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

5.2. Special hazards arising from the substance or mixture

Flammable liquid and vapour.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Ensure adequate ventilation, especially in confined areas.

Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Ground and bond container and receiving equipment.
Use explosion-proof [electrical/lighting/ventilating] equipment.
Use non-sparking tools.
Take action to prevent static discharges.
It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.
Smoking, drinking and consumption of food is not allowed in the work area.
See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Take action to prevent static discharges.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Recommended storage material: Always store in containers of the same material as the original container.

Storage conditions: Dry, cool and well ventilated

Incompatible materials: Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

propan-2-ol

Long term exposure limit (8 hours) (ppm): 400

Long term exposure limit (8 hours) (mg/m³): 999

Short term exposure limit (15 minutes) (ppm): 500

Short term exposure limit (15 minutes) (mg/m³): 1250

(2-methoxymethylethoxy)propanol

Long term exposure limit (8 hours) (ppm): 50

Long term exposure limit (8 hours) (mg/m³): 308

Annotations:

Sk = Can be absorbed through the skin and lead to systemic toxicity.

2-(2-butoxyethoxy)ethanol

Long term exposure limit (8 hours) (ppm): 10

Long term exposure limit (8 hours) (mg/m³): 67.5

Short term exposure limit (15 minutes) (ppm): 15

Short term exposure limit (15 minutes) (mg/m³): 101.2

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.

EH40/2005 Workplace exposure limits (Fourth Edition 2020).

DNEL

(2-methoxymethylethoxy)propanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	121 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	283 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	37.2 mg/m ³
Long term – Systemic effects - Workers	Inhalation	308 mg/kg
Long term – Systemic effects - General population	Oral	36 mg/kg bw/day

2-(2-butoxyethoxy)ethanol

Duration:	Route of exposure:	DNEL:
Long term – Local effects - Workers	Inhalation	67.5 mg/m ³
Short term – Local effects - Workers	Inhalation	101.2 mg/m ³
Long term – Systemic effects - General population	Oral	6,25 mg/kg bw/day

Octamethylcyclotetrasiloxane

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	13 mg/m ³
Long term – Local effects - Workers	Inhalation	73 mg/m ³
Long term – Systemic effects - General population	Inhalation	13 mg/m ³
Long term – Systemic effects - Workers	Inhalation	73 mg/m ³
Short term – Local effects - General population	Inhalation	13 mg/m ³
Short term – Local effects - Workers	Inhalation	73 mg/m ³
Short term – Systemic effects - General population	Inhalation	13 mg/m ³
Short term – Systemic effects - Workers	Inhalation	73 mg/m ³
Long term – Systemic effects - General population	Oral	3.7 mg/kg bw/day
Short term – Systemic effects - General population	Oral	3.7 mg/kg bw/day

propan-2-ol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	319 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	888 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	89 mg/m ³
Long term – Systemic effects - Workers	Inhalation	500 mg/m ³
Long term – Systemic effects - General population	Oral	26 mg/kg bw/day

PNEC

(2-methoxymethylethoxy)propanol

Route of exposure:	Duration of Exposure:	PNEC:
--------------------	-----------------------	-------

Freshwater		19 mg/L
Freshwater sediment		70.2 mg/kg
Intermittent release		190 mg/L
Marine water		1.9 mg/L
Marine water sediment		7.02 mg/kg
Sewage treatment plant		4168 mg/L
Soil		2.74 mg/kg

2-(2-butoxyethoxy)ethanol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		1.1 mg/L
Freshwater sediment		4.4 mg/kg dw
Intermittent release		11 mg/L
Marine water		0.11 mg/L
Marine water sediment		0.44 mg/kg dw
Soil		0.32 mg/kg dw

Octamethylcyclotetrasiloxane

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		0.44 µg/L
Freshwater sediment		0.59 mg/kg dw
Marine water		0.044 µg/L
Marine water sediment		0.059 mg/kg dw
Sewage treatment plant		10 mg/L
Soil		0.15 mg/kg dw

propan-2-ol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		140.9 mg/L
Freshwater sediment		552 mg/kg
Intermittent release		140.9 mg/L
Marine water		140.9 mg/L
Marine water sediment		552 mg/kg
Sewage treatment plant		2251 mg/L
Soil		28 mg/kg

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations:

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios:

There are no exposure scenarios implemented for this product.

Exposure limits:

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See

<i>Appropriate technical measures:</i>	occupational hygiene limit values above. The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked. Apply standard precautions during use of the product. Avoid inhalation of vapours.
<i>Hygiene measures:</i>	In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.
<i>Measures to avoid environmental exposure:</i>	Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

<i>Generally:</i>	Use only UKCA marked protective equipment.
<i>Respiratory Equipment:</i> No specific requirements	
<i>Skin protection:</i> No specific requirements.	
<i>Hand protection:</i>	

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	-	> 480	EN374-2, EN374-3, EN388	

Eye protection:

Type	Standards	
Safety glasses with side shields.	EN166	

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

<i>Physical state:</i>	Liquid
<i>Colour:</i>	Yellowish
<i>Odour / Odour threshold:</i>	Banana
<i>pH:</i>	4.5
<i>Density (g/cm³):</i>	0.985
<i>Kinematic viscosity:</i>	No relevant or available data due to the nature of the product.
<i>Particle characteristics:</i>	Does not apply to liquids.

Phase changes

<i>Melting point/Freezing point (°C):</i>	No relevant or available data due to the nature of the
---	--

<i>Softening point/range (°C):</i>	product.
<i>Boiling point (°C):</i>	Does not apply to liquids.
<i>Vapour pressure:</i>	No relevant or available data due to the nature of the product.
<i>Relative vapour density:</i>	No relevant or available data due to the nature of the product.
<i>Decomposition temperature (°C):</i>	No relevant or available data due to the nature of the product.

Data on fire and explosion hazards

<i>Flash point (°C):</i>	42
<i>Flammability (°C):</i>	The material is ignitable.
<i>Auto-ignition temperature (°C):</i>	No relevant or available data due to the nature of the product.
<i>Lower and upper explosion limit (% v/v):</i>	No relevant or available data due to the nature of the product.

Solubility

<i>Solubility in water:</i>	Completely soluble
<i>n-octanol/water coefficient (LogKow):</i>	No relevant or available data due to the nature of the product.
<i>Solubility in fat (g/L):</i>	No relevant or available data due to the nature of the product.

9.2. Other information

<i>Other physical and chemical parameters:</i>	No data available.
<i>Oxidizing properties:</i>	No relevant or available data due to the nature of the product.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Avoid static electricity.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance	propan-2-ol
Test method:	OECD 401
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	5840 mg/kg

Product/substance	propan-2-ol
Test method:	OECD 403
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50 (vapour)
Result:	>25 mg/L

Product/substance	propan-2-ol
Test method:	OECD 402
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	13900 mg/kg

Product/substance	(2-methoxymethylethoxy)propanol
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	>5000 mg/kg

Product/substance	(2-methoxymethylethoxy)propanol
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	9510 mg/kg

Product/substance	(2-methoxymethylethoxy)propanol
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50 (vapour)
Result:	3.35 mg/L

Product/substance	2-(2-butoxyethoxy)ethanol
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	>2000 mg/kg

Product/substance	2-(2-butoxyethoxy)ethanol
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	2764 mg/kg

Product/substance 2-(2-butoxyethoxy)ethanol
Species: Rat
Route of exposure: Inhalation
Test: LC50
Result: >29 ppm

Product/substance 2-(2-butoxyethoxy)ethanol
Species: Mouse
Route of exposure: Oral
Test: LD50
Result: 2410 mg/kg

Product/substance 1,2-benzisothiazol-3(2H)-one
Species: Rat
Route of exposure: Dermal
Test: LD50
Result: >2000 mg/kg

Product/substance 1,2-benzisothiazol-3(2H)-one
Species: Mouse
Route of exposure: Oral
Test: LD50
Result: 1150 mg/kg

Product/substance 1,2-benzisothiazol-3(2H)-one
Species: Rat
Route of exposure: Oral
Test: LD50
Result: 597 mg/kg

Product/substance 1,2-benzisothiazol-3(2H)-one
Species: Rat
Route of exposure: Dermal
Test: LD50
Result: >2000 mg/kg engångsdos ·

Product/substance 1,2-benzisothiazol-3(2H)-one
Species: Rat
Route of exposure: Oral
Test: LD50
Result: 1020 mg/kg ·

Product/substance Octamethylcyclotetrasiloxane
Species: Rat
Route of exposure: Oral
Test: LD50
Result: 4800 mg/kg

Product/substance Octamethylcyclotetrasiloxane
Species: Rat
Route of exposure: Inhalation
Test: LC50
Result: 36 mg/l, 4h ·

Product/substance Octamethylcyclotetrasiloxane
Species: Rat
Route of exposure: Dermal

Test: LD50
Result: >2400 mg/kg ·

Skin corrosion/irritation

Product/substance 2-(2-butoxyethoxy)ethanol
Test method: OECD 404
Species: Rabbit
Result: No adverse effect observed (Not irritating)

Product/substance Octamethylcyclotetrasiloxane
Test method: OECD 404
Species: Rat
Result: No adverse effect observed (Not irritating)

Serious eye damage/irritation

Product/substance 2-(2-butoxyethoxy)ethanol
Test method: OECD 404
Species: Rabbit
Result: Adverse effect observed (Irritating)

Product/substance Octamethylcyclotetrasiloxane
Test method: OECD 405
Species: Rabbit
Result: No adverse effect observed (Not irritating)

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Product/substance 2-(2-butoxyethoxy)ethanol
Test method: OECD 406
Species: Guinea pig
Result: No adverse effect observed (not sensitising)

Product/substance Octamethylcyclotetrasiloxane
Test method: OECD 406
Species: Guinea pig
Result: No adverse effect observed (not sensitising)

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

None known.

Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information

propan-2-ol has been classified by IARC as a group 3 carcinogen.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Product/substance: propan-2-ol
Species: Fish
Duration: 96 hours
Test: LC50
Result: >100 mg/L

Product/substance: propan-2-ol
Species: Algae
Duration: 8 d
Test: LOEC
Result: 1000 mg/L

Product/substance: propan-2-ol
Species: Daphnia, Daphnia magna
Duration: 48 hours
Test: LC50
Result: >100 mg/L

Product/substance: propan-2-ol
Species: Algae
Duration: 72 hours
Test: EC50
Result: >100 mg/L

Product/substance: (2-methoxymethylethoxy)propanol
Species: Fish, Poecilia reticulata
Duration: 96 hours
Test: LC50
Result: >1000 mg/L

Product/substance: (2-methoxymethylethoxy)propanol
Species: Daphnia, Daphnia magna
Duration: 48 hours
Test: EC50
Result: 1919 mg/L

Product/substance: (2-methoxymethylethoxy)propanol
Species: Daphnia, Daphnia magna
Duration: 22 d
Test: NOEC
Result: 0.5 mg/L

Product/substance: (2-methoxymethylethoxy)propanol
Species: Algae, Pseudokirchneriella subcapitata
Duration: 72 hours
Test: EC50

Result: >969 mg/L

Product/substance 2-(2-butoxyethoxy)ethanol
Species: Fish, *Leuciscus idus*
Duration: 96 hours
Test: LC50
Result: >100 mg/L

Product/substance 2-(2-butoxyethoxy)ethanol
Species: Algae, *Scenedesmus subspicatus*
Duration: 96 hours
Test: EC50
Result: >100 mg/L

Product/substance 2-(2-butoxyethoxy)ethanol
Species: *Daphnia*, *Daphnia magna*
Duration: 48 hours
Test: EC50
Result: >100 mg/L

Product/substance 1,2-benzisothiazol-3(2H)-one
Species: *Daphnia*, *Daphnia magna*
Duration: 48 hours
Test: EC50
Result: 2.44 mg/L

Product/substance 1,2-benzisothiazol-3(2H)-one
Species: Fish
Duration: 96 hours
Test: LC50
Result: 0.74 mg/L

Product/substance Octamethylcyclotetrasiloxane
Species: Fish, *Oncorhynchus mykiss*
Duration: 96 hours
Test: LC50
Result: >0.022 mg/L

Product/substance Octamethylcyclotetrasiloxane
Species: *Daphnia*, *Daphnia magna*
Duration: 48 hours
Test: EC50
Result: 0.015 mg/L

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

Product/substance propan-2-ol
Conclusion: Readily biodegradable

Product/substance (2-methoxymethylethoxy)propanol
Result: 75%
Conclusion: Readily biodegradable
Test: OECD 301 F

Product/substance 2-(2-butoxyethoxy)ethanol
Result: 100%
Conclusion: Readily biodegradable

Test: OECD 301 E

12.3. Bioaccumulative potential

Product/substance propan-2-ol
LogKow: 0.0500
Conclusion: No potential for bioaccumulation

Product/substance (2-methoxymethylethoxy)propanol
LogKow: 0.0060
Conclusion: No potential for bioaccumulation

Product/substance 2-(2-butoxyethoxy)ethanol
LogKow: 1.0000
Conclusion: No potential for bioaccumulation

Product/substance 1,2-benzisothiazol-3(2H)-one
LogKow: 1.4
Conclusion: No potential for bioaccumulation

Product/substance Octamethylcyclotetrasiloxane
BCF: 12400
LogKow: 5.1000
Conclusion: Potential for bioaccumulation

12.4. Mobility in soil

(2-methoxymethylethoxy)propanol
LogKoc = 0.28, High mobility potential.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste. (*)

HP 3 - Flammable

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

EWC code: 07 06 04* Other organic solvents, washing liquids and mother liquors

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: TRANSPORT INFORMATION

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other informat ion:
ADR	UN1993	FLAMMABLE LIQUID, N.O.S. (propan-2-ol)	Transport hazard class: 3 Label: 3 Classification code: F1 	III	No	Limited quantities: 5 L Tunnel restriction code: (D/E) See below for additional information.
IMDG	UN1993	FLAMMABLE LIQUID, N.O.S. (propan-2-ol)	Transport hazard class: 3 Label: 3 Classification code: F1 	III	No	Limited quantities: 5 L EmS: F-E S-E See below for additional information.
IATA	UN1993	FLAMMABLE LIQUID, N.O.S. (propan-2-ol)	Transport hazard class: 3 Label: 3 Classification code: F1 	III	No	See below for additional information.

* Packing group

** Environmental hazards

Additional information

This product is within scope of the regulations of transport of dangerous goods.

ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in

connection with transport.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application:

No special.

Demands for specific education:

No specific requirements.

SEVESO - Categories / dangerous substances:

P5c - FLAMMABLE LIQUIDS, Qualifying quantity (lower-tier): 5.000 tonnes / (upper-tier): 50.000 tonnes

REACH, Annex XVII:

2-(2-butoxyethoxy)ethanol is subject to restrictions, UK-REACH annex XVII (entry 55).
Octamethylcyclotetrasiloxane is subject to restrictions, UK-REACH annex XVII (entry 70).
propan-2-ol is subject to UK-REACH restrictions (entry 40).
Octamethylcyclotetrasiloxane is subject to UK-REACH restrictions (entry 40).

Additional information:

Not applicable.

Sources:

The Health and Safety at Work etc. Act 1974 Regulations 2013.
Control of Major Accident Hazards (COMAH) Regulations 2015.
Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.
Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.
Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: OTHER INFORMATION

Full text of H-phrases as mentioned in section 3

H225, Highly flammable liquid and vapour.
H226, Flammable liquid and vapour.
H302, Harmful if swallowed.
H315, Causes skin irritation.
H317, May cause an allergic skin reaction.
H318, Causes serious eye damage.
H319, Causes serious eye irritation.
H336, May cause drowsiness or dizziness.
H361f, Suspected of damaging fertility.

H400, Very toxic to aquatic life.
H410, Very toxic to aquatic life with long lasting effects.
H411, Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CE = Conformité Européenne (European conformity)
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
CSA = Chemical Safety Assessment
CSR = Chemical Safety Report
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EINECS = European Inventory of Existing Commercial chemical Substances
ES = Exposure Scenario
EUH statement = CLP-specific Hazard statement
EuPCS = European Product Categorisation System
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
GWP = Global warming potential
IARC = International Agency for Research on Cancer (IARC)
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the mixture in regard to physical hazards has been based on experimental data.

The safety data sheet is validated by

-

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product.

Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en